## & alphafence

Alfalfa Ltd t/a AlphaFence The Granary, Ty Coch Upper Llanover Abergavenny, NP7 9LA Tel: 01873 880784 info@alphafence.co.uk www.alphafence.co.uk

## SPORTS & SECURITY FENCING SERVICES

## HEAVY DUTY BOOT BRUSH

Boot brushes are widely used at the entrance to synthetic and other sports facilities, to encourage users to remove mud and debris before entering the facility and contaminating the surface.

AlphaFence have developed a heavy duty brush unit, available in single or double width, to cope with the demands

Height: Width:	1000 mm (to Grab Rail). 1020 mm.
Frame:	80 x 40 mm Rectangular Hollow Section Steel, fully welded, steel capped, and uprights extended below ground and cast into 300 x 300 x 550 mm concrete foundations.
Grab Rail:	48.3 mm Circular Hollow Section Steel Tube, fully welded between vertical frame members.
Lower Brush:	914 x 100 x 100 mm Polypropylene rigid-bristle Platform Broom with wooden base, bolted to lower horizontal with galvanised M8 bolts, nylock nuts and large washers.
Side Brush:	228 x 59 x 37 mm Bassine rigid-bristle Scrub Brush with wooden base, and side mounted similarly.

Finish: Hot Dip Galvanised after manufacture. Option for coloured Polyester Powder Coating.



## NOTES & CHARACTERISTICS:

- Each unit is constructed from a substantial welded steel frame, supported by two vertical extensions set firmly into concrete foundations.
- Galvanised (and optionally colour coated), the unit will not rust nor lose its finish for decades (under normal circumstances).
- The stiff polypropylene bristles are durable and effective.
- The brush-heads are bolted onto the frame, and can thus be easily replaced when eventually worn.
- The brush unit can be colour matched to the adjacent fencing and gates, enabling them to blend in to their environment.
- They are much more cost effective than alternate grille-based cleaning grids.

